

## Prestatieverklaring

### Keilboutanker BZ

geldig voor  
MÜPRO Keilboutanker BZ

Dit document van MÜPRO geldt alleen ter informatie en is niet onderworpen aan veranderingen.  
De totale inhoud mag alleen voor reclame of andere doeleinden gebruikt worden indien Müpro hiervoor toestemming verleent. Alle rechten voorbehouden.

### Prestatieverklaring conform verordening (EU) Nr. 305/2011

DoP Nr. MP Hochleistungsanker 20160824

#### 1. Unieke identificatiecode van het producttype:

MÜPRO Keilboutanker BZ en BZ-IG

#### 2. Type-, charge- of serienummer, dan wel een ander identificatiemiddel voor het bouwproduct, zoals voorgeschreven in artikel 11, lid 4:

ETA-05/0158, bijlage A3 en A5  
Chargennummer: zie verpakking

#### 3. Beoogde gebruik van het bouwproduct, overeenkomstig de toepasselijke geharmoniseerde technische specificatie, zoals door de fabrikant bepaald:

<b>Producttype</b>	Spreidanker met gecontroleerd draaimoment (bouttype (met binnendraad))
<b>Voor toepassing in</b>	Gescheurd en ongescheurd beton C20/25 - C50/60 (EN 206)
<b>Optie</b>	1
<b>Belasting</b>	Statisch en quasi-statisch Seismisch, categorie C1+C2 (inbegrepen maten BZ plus M8, M10, M12, M16, M20)
<b>Materiaal</b>	<p><u>Staal verzinkt:</u> alleen in droge binnenruimtes inbegrepen maten: BZ: M8, M10, M12, M16, M20, M24, M27 BZ-IG: M6, M8, M10, M12</p> <p><u>Staal verzinkt diffusie:</u> alleen in droge binnenruimtes inbegrepen maten: BZ: M10, M12, M16, M20</p> <p><u>Roestvaststaal (markering A4) (3.16):</u> voor binnen- en buitenbereiken zonder bijzondere agressieve omstandigheden inbegrepen maten: BZ: M8, M10, M12, M16, M20, M24 BZ-IG: M6, M8, M10, M12</p> <p><u>Hoog-corrosiebestendig staal (markering HCR):</u> voor binnen- en buitenbereiken onder bijzondere agressieve omstandigheden inbegrepen maten: BZ: M8, M10, M12, M16, M20, M24 BZ-IG: M6, M8, M10, M12</p>
<b>Temperatuurbereik (indien van toepassing)</b>	--

#### 4. Naam, geregistreerde handelsnaam of geregistreerd handelsmerk en contactadres van de fabrikant, zoals voorgeschreven in artikel 11, lid 5:

MÜPRO Services GmbH  
Hessenstrasse 11  
D - 65719 Hofheim-Wallau

#### 5. Indien van toepassing, naam en contactadres van de gemachtigde wiens mandaat de in artikel 12, lid 2, vermelde taken bestrijkt:

-

**6. Het systeem of de systemen voor de beoordeling en verificatie van de prestatiebestendigheid van het bouwproduct, vermeld in bijlage V:**

System 1

**7. Indien de prestatieverklaring betrekking heeft op een bouwproduct dat onder een geharmoniseerde norm valt:**

-

**8. Indien de prestatieverklaring betrekking heeft op een bouwproduct waarvoor een Europese technische beoordeling is afgegeven:**

Deutsches Institut für Bautechnik, Berlin

heeft het volgende afgegeven:

ETA-05/0158

op basis van

ETAG 001-2

De aangemelde instantie voor productcertificering 0756-CPD heeft het volgende uitgevoerd volgens systeem 1:

- i) de bepaling van het producttype op grond van type onderzoek (inclusief bemonstering), typeberekening, getabelleerde waarden of een beschrijvende documentatie van het product;
- ii) de initiële inspectie van de productie-installatie en van de productiecontrole in de fabriek;
- iii) permanente bewaking, beoordeling en evaluatie van de productiecontrole in de fabriek

en heeft het volgende afgegeven: Certificaat van prestatiebestendigheid 1343-CPR-M552-1



### 9. Aangegeven prestatie

Essentiële kenmerken	Beoordelingsmethode	Prestatie		Geharmoniseerde technische specificaties
		BZ	BZ-IG	
Karakteristieke trekweerstand	ETAG 001, bijlage C CEN/TS 1992-4	ETA-05/0158, bijlage C1-C4	ETA-05/0158, bijlage C11-C12	ETAG 001
Karakteristieke afschuifweerstand	ETAG 001, bijlage C CEN/TS 1992-4	ETA-05/0158, bijlage C5	ETA-05/0158, bijlage C13	
Karakteristieke seismische weerstand	TR 045	ETA-05/0158 bijlage C6	NPD	
Verschuiving in gebruikstoestand	ETAG 001, bijlage C CEN/TS 1992-4	ETA-05/0158, bijlage C9- C10	ETA-05/0158, bijlage C15	
Karakteristieke brandweerstand	TR 020 CEN/TS 1992-4	ETA-05/0158, bijlage C7-C8	ETA-05/0158, bijlage C14	

Indien overeenkomstig artikel 37 of 38 een specifieke technische documentatie is gebruikt, de eisen waaraan het product voldoet: --

### 10. De prestatie van het in de punten 1 en 2 omschreven product zijn conform de in punt 9 aangegeven prestaties

Deze prestatieverklaring wordt verstrekt onder de exclusieve verantwoordelijkheid van de in punt 4 vermelde fabrikant.

Ondertekend voor en namens de fabrikant door:



Hofheim-Wallau, 24.08.2016

i.V. Stefan Podszus,  
Kwaliteitsmanager

**Table C1: Characteristic values for tension loads, BZ zinc plated, cracked concrete, static and quasi-static action**

Anchor size			M8	M10	M12	M16	M20	M24	M27
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,0						
<b>Steel failure</b>									
Characteristic tension resistance	$N_{Rk,s}$	[kN]	16	27	40	60	86	126	196
Partial safety factor	$\gamma_{Ms}$	[-]	1,53		1,5		1,6	1,5	
<b>Pull-out</b>									
<b>Standard anchorage depth</b>									
Characteristic resistance in concrete C20/25	$N_{Rk,p}$	[kN]	5	9	16	25	1)	1)	1)
<b>Reduced anchorage depth</b>									
Characteristic resistance in concrete C20/25	$N_{Rk,p}$	[kN]	5	7,5	1)	1)	-	-	-
Increasing factor for $N_{Rk,p}$	$\psi_c$	[-]	$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$						
<b>Concrete cone failure</b>									
Effective anchorage depth	$h_{ef}$	[mm]	46	60	70	85	100	115	125
Reduced anchorage depth	$h_{ef,red}$	[mm]	35 <sup>2)</sup>	40	50	65	-	-	-
Factor acc. to CEN/TS 1992-4	$k_{cr}$	[-]	7,2						

<sup>1)</sup> Pull-out is not decisive.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

**Heavy duty anchor BZ**

**Performance**  
Characteristic values for tension loads, BZ zinc plated, cracked concrete, static and quasi-static action

**Annex C1**

**Table C2: Characteristic values for tension loads, BZ A4 / HCR, cracked concrete, static and quasi-static action**

Anchor size			M8	M10	M12	M16	M20	M24
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,0					
<b>Steel failure</b>								
Characteristic tension resistance	$N_{Rk,s}$	[kN]	16	27	40	64	108	110
Partial safety factor	$\gamma_{Ms}$	[-]	1,5				1,68	1,5
<b>Pull-out</b>								
<b>Standard anchorage depth</b>								
Characteristic resistance in concrete C20/25	$N_{Rk,p}$	[kN]	5	9	16	25	<sup>1)</sup>	40
<b>Reduced anchorage depth</b>								
Characteristic resistance in concrete C20/25	$N_{Rk,p}$	[kN]	5	7,5	<sup>1)</sup>	<sup>1)</sup>	-	-
Increasing factor for $N_{Rk,p}$	$\psi^c$	[-]	$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$					
<b>Concrete cone failure</b>								
Effective anchorage depth	$h_{ef}$	[mm]	46	60	70	85	100	125
Reduced anchorage depth	$h_{ef,red}$	[mm]	35 <sup>2)</sup>	40	50	65	-	-
Factor according to CEN/TS 1992-4	$k_{cr}$	[-]	7,2					

<sup>1)</sup> Pull-out is not decisive.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

**Heavy duty anchor BZ**

**Performance**  
Characteristic values for tension loads, BZ A4 / HCR,  
cracked concrete, static and quasi-static action

**Annex C2**

**Table C3: Characteristic values for tension loads, BZ zinc plated, non-cracked concrete, static and quasi-static action**

Anchor size		M8	M10	M12	M16	M20	M24	M27
Installation safety factor	$\gamma_2 = \gamma_{inst}$ [-]	1,0						
<b>Steel failure</b>								
Characteristic tension resistance	$N_{Rk,s}$ [kN]	16	27	40	60	86	126	196
Partial safety factor	$\gamma_{Ms}$ [-]	1,53		1,5		1,6	1,5	
<b>Pull-out</b>								
<b>Standard anchorage depth</b>								
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,p}$ [kN]	12	16	25	35	1)	1)	1)
<b>Reduced anchorage depth</b>								
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,p}$ [kN]	7,5	9	1)	1)	-	-	-
<b>Splitting</b> For the proof against splitting failure $N_{Rk,c}^0$ has to be replaced by $N_{Rk,sp}^0$ with consideration of the member thickness								
<b>Standard anchorage depth</b>								
Splitting for <b>standard thickness of concrete member</b> (The higher resistance of case 1 and case 2 may be applied; the values $s_{cr,sp}$ and $c_{cr,sp}$ may be linearly interpolated for the member thickness $h_{min,2} < h < h_{min,1}$ (Case 2); $\psi_{h,sp} = 1,0$ )								
Standard thickness of concrete	$h_{min,1} \geq$ [mm]	100	120	140	170	200	230	250
<b>Case 1</b>								
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,sp}^0$ [kN]	9	12	20	30	40	62,3	50
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$ [mm]	3 $h_{ef}$						
<b>Case 2</b>								
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,sp}^0$ [kN]	12	16	25	35	50,5	62,3	70,6
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$ [mm]	4 $h_{ef}$				4,4 $h_{ef}$	3 $h_{ef}$	5 $h_{ef}$
<b>Splitting for minimum thickness of concrete member</b>								
Minimum thickness of concrete	$h_{min,2} \geq$ [mm]	80	100	120	140			
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,sp}^0$ [kN]	12	16	25	35	-	-	-
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$ [mm]	5 $h_{ef}$						
<b>Reduced anchorage depth</b>								
Minimum thickness of concrete	$h_{min,3} \geq$ [mm]	80	80	100	140			
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,sp}^0$ [kN]	7,5	9	17,9	26,5	-	-	-
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$ [mm]	200	200	250	300			
Increasing factor for $N_{Rk,p}$ and $N_{Rk,sp}^0$	$\psi_c$ [-]	$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$						
<b>Concrete cone failure</b>								
Effective anchorage depth	$h_{ef}$ [mm]	46	60	70	85	100	115	125
Reduced anchorage depth	$h_{ef,red}$ [mm]	35 <sup>2)</sup>	40	50	65	-	-	-
Factor according to CEN/TS 1992-4	$k_{ucr}$ [-]	10,1						

<sup>1)</sup> Pull-out is not decisive.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

**Heavy duty anchor BZ**

**Performance**  
Characteristic values for tension loads, BZ zinc plated, non-cracked concrete, static and quasi-static action

**Annex C3**



**Table C4: Characteristic values for tension loads, BZ A4 / HCR, non-cracked concrete, static and quasi-static action**

Anchor size			M8	M10	M12	M16	M20	M24
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,0					
<b>Steel failure</b>								
Characteristic tension resistance	$N_{Rk,s}$	[kN]	16	27	40	64	108	110
Partial safety factor	$\gamma_{Ms}$	[-]	1,5				1,68	1,5
<b>Pull-out</b>								
<b>Standard anchorage depth</b>								
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,p}$	[kN]	12	16	25	35	1)	1)
<b>Reduced anchorage depth</b>								
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,p}$	[kN]	7,5	9	1)	1)	-	-
<b>Splitting</b> For the proof against splitting failure $N_{Rk,c}^0$ has to be replaced by $N_{Rk,sp}^0$ with consideration of the member thickness								
<b>Standard anchorage depth</b>								
Splitting for standard thickness of concrete member (The higher resistance of case 1 and case 2 may be applied; the values $s_{cr,sp}$ and $c_{cr,sp}$ may be linearly interpolated for the member thickness $h_{min,2} < h < h_{min,1}$ (Case 2); $\psi_{h,sp} = 1,0$ )								
Standard thickness of concrete	$h_{min,1} \geq$	[mm]	100	120	140	160	200	250
<b>Case 1</b>								
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,sp}^0$	[kN]	9	12	20	30	40	-
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]	3 $h_{ef}$					
<b>Case 2</b>								
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,sp}^0$	[kN]	12	16	25	35	50,5	70,6
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]	230	250	280	400	440	500
<b>Splitting for minimum thickness of concrete member</b>								
Minimum thickness of concrete	$h_{min,2} \geq$	[mm]	80	100	120	140		
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,sp}^0$	[kN]	12	16	25	35	-	-
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]	5 $h_{ef}$					
<b>Reduced anchorage depth</b>								
Minimum thickness of concrete	$h_{min,3} \geq$	[mm]	80	80	100	140		
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,sp}^0$	[kN]	7,5	9	17,9	26,5	-	-
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]	200	200	250	300		
Increasing factor for $N_{Rk,p}$ and $N_{Rk,sp}^0$	$\psi_c$	[-]	$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$					
<b>Concrete cone failure</b>								
Effective anchorage depth	$h_{ef}$	[mm]	46	60	70	85	100	125
Reduced anchorage depth	$h_{ef,red}$	[mm]	35 <sup>2)</sup>	40	50	65	-	-
Factor according to CEN/TS 1992-4	$k_{ucr}$	[-]	10,1					

<sup>1)</sup> Pull-out is not decisive.

<sup>2)</sup> Use restricted to anchoring of structural components statically indeterminate.

**Heavy duty anchor BZ**

**Performance**  
Characteristic values for tension loads, BZ A4 / HCR, non-cracked concrete, static and quasi-static action

**Annex C4**



**Table C5: Characteristic values for shear loads, BZ, cracked and non-cracked concrete, static or quasi static action**

Anchor size			M8	M10	M12	M16	M20	M24	M27	
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,0							
<b>Steel failure without lever arm, Steel zinc plated</b>										
Characteristic shear resistance	$V_{Rk,s}$	[kN]	12,2	20,1	30	55	69	114	169,4	
Factor for ductility	$k_2$	[-]	1,0							
Partial safety factor	$\gamma_{Ms}$	[-]	1,25				1,33	1,25	1,25	
<b>Steel failure without lever arm, Stainless steel A4, HCR</b>										
Characteristic shear resistance	$V_{Rk,s}$	[kN]	13	20	30	55	86	123,6	-	
Factor for ductility	$k_2$	[-]	1,0							
Partial safety factor	$\gamma_{Ms}$	[-]	1,25				1,4	1,25		
<b>Steel failure with lever arm, Steel zinc plated</b>										
Characteristic bending resistance	$M_{Rk,s}^D$	[Nm]	23	47	82	216	363	898	1331,5	
Partial safety factor	$\gamma_{Ma}$	[-]	1,25				1,33	1,25	1,25	
<b>Steel failure with lever arm, Stainless steel A4, HCR</b>										
Characteristic bending resistance	$M_{Rk,s}^D$	[Nm]	26	52	92	200	454	785,4	-	
Partial safety factor	$\gamma_{Ma}$	[-]	1,25				1,4	1,25		
<b>Concrete pry-out failure</b>										
Factor k acc. to ETAG 001, Annex C or $k_3$ acc. to CEN/TS 1992-4	$k_{(3)}$	[-]	2,4				2,8			
<b>Concrete edge failure</b>										
Effective length of anchor in shear loading with $h_{ef}$	Steel zinc plated	$l_f$	[mm]	46	60	70	85	100	115	125
	Stainless steel A4, HCR	$l_f$	[mm]	46	60	70	85	100	125	-
Effective length of anchor in shear loading with $h_{ef,red}$	Steel zinc plated	$l_{f,red}$	[mm]	35 <sup>1)</sup>	40	50	65	-	-	-
	Stainless steel A4, HCR	$l_{f,red}$	[mm]	35 <sup>1)</sup>	40	50	65			
Outside diameter of anchor	$d_{nom}$	[mm]	8	10	12	16	20	24	27	

<sup>1)</sup> Use restricted to anchoring of structural components statically indeterminate.

**Heavy duty anchor BZ**

**Performance**  
Characteristic values for shear loads, BZ, cracked and non-cracked concrete, static or quasi static action

**Annex C5**

**Table C6: Characteristic resistance for seismic loading, BZ,  
standard anchorage depth, performance category C1 and C2**

Anchor size		M8	M10	M12	M16	M20
<b>Tension loads</b>						
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,0			
<b>Steel failure, Steel zinc plated</b>						
Characteristic resistance C1	$N_{Rk,s,seis,C1}$	[kN]	16	27	40	60
Characteristic resistance C2	$N_{Rk,s,seis,C2}$	[kN]	16	27	40	60
Partial safety factor	$\gamma_{Ms,seis}$	[-]	1,53		1,5	
<b>Steel failure, Stainless steel A4, HCR</b>						
Characteristic resistance C1	$N_{Rk,s,seis,C1}$	[kN]	16	27	40	64
Characteristic resistance C2	$N_{Rk,s,seis,C2}$	[kN]	16	27	40	64
Partial safety factor	$\gamma_{Ms,seis}$	[-]	1,5			1,68
<b>Pull-out (steel zinc plated, stainless steel A4 and HCR)</b>						
Characteristic resistance C1	$N_{Rk,p,seis,C1}$	[kN]	5	9	16	25
Characteristic resistance C2	$N_{Rk,p,seis,C2}$	[kN]	2,3	3,6	10,2	13,8
Increasing factor for $N_{Rk,p}$	$\psi_c$	[-]	1,0			
<b>Shear loads</b>						
<b>Steel failure without lever arm, Steel zinc plated</b>						
Characteristic resistance C1	$V_{Rk,s,seis,C1}$	[kN]	9,3	20	27	44
Characteristic resistance C2	$V_{Rk,s,seis,C2}$	[kN]	6,7	14	16,2	35,7
Partial safety factor	$\gamma_{Ms,seis}$	[-]	1,25			1,33
<b>Steel failure without lever arm, Stainless steel A4, HCR</b>						
Characteristic resistance C1	$V_{Rk,s,seis,C1}$	[kN]	9,3	20	27	44
Characteristic resistance C2	$V_{Rk,s,seis,C2}$	[kN]	6,7	14	16,2	35,7
Partial safety factor	$\gamma_{Ms,seis}$	[-]	1,25			1,4

**Heavy duty anchor BZ**

**Performance**  
Characteristic resistance for seismic loading, BZ,  
standard anchorage depth, performance category C1 and C2

**Annex C6**

**Table C7: Characteristic values for tension and shear load under fire exposure, BZ, standard anchorage depth, cracked and non-cracked concrete C20/25 to C50/60**

Anchor size		M8	M10	M12	M16	M20	M24	M27		
<b>Tension load</b>										
<b>Steel failure</b>										
<b>Steel, galvanised</b>										
Characteristic resistance	R30	$N_{Rk,s,fi}$	[kN]	1,5	2,6	4,1	7,7	9,4	13,6	17,6
	R60			1,1	1,9	3,0	5,6	8,2	11,8	15,3
	R90			0,8	1,4	2,4	4,4	6,9	10,0	13,0
	R120			0,7	1,2	2,2	4,0	6,3	9,1	11,8
<b>Stainless steel A4, HCR</b>										
Characteristic resistance	R30	$N_{Rk,s,fi}$	[kN]	3,8	6,9	12,7	23,7	33,5	48,2	-
	R60			2,9	5,3	9,4	17,6	25,0	35,9	
	R90			2,0	3,6	6,1	11,5	16,4	23,6	
	R120			1,6	2,8	4,5	8,4	12,1	17,4	
<b>Shear load</b>										
<b>Steel failure without lever arm</b>										
<b>Steel, galvanised</b>										
Characteristic resistance	R30	$V_{Rk,s,fi}$	[kN]	1,6	2,6	4,1	7,7	11	16	20,6
	R60			1,5	2,5	3,6	6,8	11	15	19,8
	R90			1,2	2,1	3,5	6,5	10	15	19,0
	R120			1,0	2,0	3,4	6,4	10	14	18,6
<b>Stainless steel A4, HCR</b>										
Characteristic resistance	R30	$V_{Rk,s,fi}$	[kN]	3,8	6,9	12,7	23,7	33,5	48,2	-
	R60			2,9	5,3	9,4	17,6	25,0	35,9	
	R90			2,0	3,6	6,1	11,5	16,4	23,6	
	R120			1,6	2,8	4,5	8,4	12,1	17,4	
<b>Steel failure with lever arm</b>										
<b>Steel, galvanised</b>										
Characteristic resistance	R30	$M^0_{Rk,s,fi}$	[Nm]	1,7	3,3	6,4	16,3	29	50	75
	R60			1,6	3,2	5,6	14	28	48	72
	R90			1,2	2,7	5,4	14	27	47	69
	R120			1,1	2,5	5,3	13	26	46	68
<b>Stainless steel A4, HCR</b>										
Characteristic resistance	R30	$M^0_{Rk,s,fi}$	[Nm]	3,8	9,0	19,7	50,1	88,8	153,5	-
	R60			2,9	6,8	14,6	37,2	66,1	114,3	
	R90			2,1	4,7	9,5	24,2	43,4	75,1	
	R120			1,6	3,6	7,0	17,8	32,1	55,5	

The characteristic resistance for pull-out failure, concrete cone failure, concrete pry-out and concrete edge failure can be calculated according to TR020 / CEN/TS 1992-4. If pull-out is not decisive in Eq. 2.4 and Eq. 2.5, TR 020  $N_{Rk,p}$  must be replaced by  $N^0_{Rk,c}$ .

**Heavy duty anchor BZ**

**Performance**

Characteristic values for tension and shear load under fire exposure, BZ, standard anchorage depth, cracked and non-cracked concrete C20/25 to C50/60

**Annex C7**



**Table C8: Characteristic values for tension and shear load under fire exposure, BZ, reduced anchorage depth, cracked and non-cracked concrete C20/25 to C50/60**

Anchor size		M8	M10	M12	M16		
<b>Tension load</b>							
<b>Steel failure</b>							
<b>Steel, galvanised</b>							
Characteristic resistance	R30	$N_{Rk,s,fi}$	[kN]	1,5	2,6	4,1	7,7
	R60			1,1	1,9	3,0	5,6
	R90			0,8	1,3	1,9	3,5
	R120			0,6	1,0	1,3	2,5
<b>Stainless steel A4, HCR</b>							
Characteristic resistance	R30	$N_{Rk,s,fi}$	[kN]	3,2	6,9	12,7	23,7
	R60			2,5	5,3	9,4	17,6
	R90			1,9	3,6	6,1	11,5
	R120			1,6	2,8	4,5	8,4
<b>Shear load</b>							
<b>Steel failure without lever arm</b>							
<b>Steel, galvanised</b>							
Characteristic resistance	R30	$V_{Rk,s,fi}$	[kN]	1,5	2,6	4,1	7,7
	R60			1,1	1,9	3,0	5,6
	R90			0,8	1,3	1,9	3,5
	R120			0,6	1,0	1,3	2,5
<b>Stainless steel A4, HCR</b>							
Characteristic resistance	R30	$V_{Rk,s,fi}$	[kN]	3,2	6,9	12,7	23,7
	R60			2,5	5,3	9,4	17,6
	R90			1,9	3,6	6,1	11,5
	R120			1,6	2,8	4,5	8,4
<b>Steel failure with lever arm</b>							
<b>Steel, galvanised</b>							
Characteristic resistance	R30	$M^0_{Rk,s,fi}$	[Nm]	1,5	3,3	6,4	16,3
	R60			1,2	2,5	4,7	11,9
	R90			0,8	1,7	3,0	7,5
	R120			0,6	1,2	2,1	5,3
<b>Stainless steel A4, HCR</b>							
Characteristic resistance	R30	$M^0_{Rk,s,fi}$	[Nm]	3,2	8,9	19,7	50,1
	R60			2,6	6,8	14,6	37,2
	R90			2,0	4,7	9,5	24,2
	R120			1,6	3,6	7,0	17,8

The characteristic resistance for pull-out failure, concrete cone failure, concrete pry-out and concrete edge failure can be calculated according to TR020 / CEN/TS 1992-4. If pull-out is not decisive in Eq. 2.4 and Eq. 2.5, TR 020  $N_{Rk,p}$  must be replaced by  $N^0_{Rk,c}$ .

**Heavy duty anchor BZ**

**Performance**  
Characteristic values for tension and shear load under fire exposure, BZ, reduced anchorage depth, cracked and non-cracked concrete C20/25 to C50/60

**Annex C8**

**Table C9: Displacements under tension load, BZ**

Anchor size			M8	M10	M12	M16	M20	M24	M27
<b>Standard anchorage depth</b>									
<b>Steel zinc plated</b>									
Tension load in cracked concrete	N	[kN]	2,4	4,3	7,6	11,9	17,1	21,1	24
Displacement	$\delta_{N0}$	[mm]	0,6	1,0	0,4	1,0	0,9	0,7	0,9
	$\delta_{N\infty}$	[mm]	1,4	1,2	1,4	1,3	1,0	1,2	1,4
Tension load in non-cracked concrete	N	[kN]	5,7	7,6	11,9	16,7	23,8	29,6	34
Displacement	$\delta_{N0}$	[mm]	0,4	0,5	0,7	0,3	0,4	0,5	0,3
	$\delta_{N\infty}$	[mm]	0,8		1,4	0,8			1,4
<b>Displacements under seismic tension loads C2</b>									
Displacements for DLS	$\delta_{N,seis,C2(DLS)}$	[mm]	2,3	4,1	4,9	3,6	5,1	-	-
Displacements for ULS	$\delta_{N,seis,C2(ULS)}$	[mm]	8,2	13,8	15,7	9,5	15,2	-	-
<b>Stainless steel A4, HCR</b>									
Tension load in cracked concrete	N	[kN]	2,4	4,3	7,6	11,9	17,1	19,0	-
Displacement	$\delta_{N0}$	[mm]	0,7	1,8	0,4	0,7	0,9	0,5	-
	$\delta_{N\infty}$	[mm]	1,2	1,4	1,4	1,4	1,0	1,8	-
Tension load in non-cracked concrete	N	[kN]	5,8	7,6	11,9	16,7	23,8	33,5	-
Displacement	$\delta_{N0}$	[mm]	0,6	0,5	0,7	0,2	0,4	0,5	-
	$\delta_{N\infty}$	[mm]	1,2	1,0	1,4	0,4	0,8	1,1	-
<b>Displacements under seismic tension loads C2</b>									
Displacements for DLS	$\delta_{N,seis,C2(DLS)}$	[mm]	2,3	4,1	4,9	3,6	5,1	-	-
Displacements for ULS	$\delta_{N,seis,C2(ULS)}$	[mm]	8,2	13,8	15,7	9,5	15,2	-	-
<b>Reduced anchorage depth</b>									
<b>Steel zinc plated, stainless steel A4, HCR</b>									
Tension load in cracked concrete	N	[kN]	2,4	3,6	6,1	9,0	-	-	-
Displacement	$\delta_{N0}$	[mm]	0,8	0,7	0,5	1,0	-	-	-
	$\delta_{N\infty}$	[mm]	1,2	1,0	0,8	1,1	-	-	-
Tension load in non-cracked concrete	N	[kN]	3,7	4,3	8,5	12,6	-	-	-
Displacement	$\delta_{N0}$	[mm]	0,1	0,2	0,2	0,2	-	-	-
	$\delta_{N\infty}$	[mm]	0,7	0,7	0,7	0,7	-	-	-

**Heavy duty anchor BZ**

Performance  
Displacements under tension load

**Annex C9**

**Table C10: Displacements under shear load, BZ**

Anchor size			M8	M10	M12	M16	M20	M24	M27
<b>Standard anchorage depth</b>									
<b>Steel zinc plated</b>									
Shear load in cracked and non-cracked concrete	V	[kN]	6,9	11,4	17,1	31,4	36,8	64,9	96,8
Displacement	$\delta_{V0}$	[mm]	2,0	3,2	3,6	3,5	1,8	3,5	3,6
	$\delta_{V\infty}$	[mm]	3,0	4,7	5,5	5,3	2,7	5,3	5,4
<b>Displacements under seismic shear loads C2</b>									
Displacements for DLS	$\delta_{V,seis,C2(DLS)}$	[mm]	3,0	2,7	3,5	4,3	4,7	-	-
Displacements for ULS	$\delta_{V,seis,C2(ULS)}$	[mm]	5,9	5,3	9,5	9,6	10,1	-	-
<b>Stainless steel A4, HCR</b>									
Shear load in cracked and non-cracked concrete	V	[kN]	7,3	11,4	17,1	31,4	43,8	70,6	-
Displacement	$\delta_{V0}$	[mm]	1,9	2,4	4,0	4,3	2,9	2,8	-
	$\delta_{V\infty}$	[mm]	2,9	3,6	5,9	6,4	4,3	4,2	-
<b>Displacements under seismic shear loads C2</b>									
Displacements for DLS	$\delta_{V,seis,C2(DLS)}$	[mm]	3,0	2,7	3,5	4,3	4,7	-	-
Displacements for ULS	$\delta_{V,seis,C2(ULS)}$	[mm]	5,9	5,3	9,5	9,6	10,1	-	-
<b>Reduced anchorage depth</b>									
<b>Steel zinc plated</b>									
Shear load in cracked and non-cracked concrete	V	[kN]	6,9	11,4	17,1	31,4	-	-	-
Displacement	$\delta_{V0}$	[mm]	2,0	3,2	3,6	3,5	-	-	-
	$\delta_{V\infty}$	[mm]	3,0	4,7	5,5	5,3	-	-	-
<b>Stainless steel A4, HCR</b>									
Shear load in cracked and non-cracked concrete	V	[kN]	7,3	11,4	17,1	31,4	-	-	-
Displacement	$\delta_{V0}$	[mm]	1,9	2,4	4,0	4,3	-	-	-
	$\delta_{V\infty}$	[mm]	2,9	3,6	5,9	6,4	-	-	-
<b>Heavy duty anchor BZ</b>								<b>Annex C10</b>	
<b>Performance</b> Displacements under shear load									



**Table C11: Characteristic values for tension loads, BZ-IG, cracked concrete, static and quasi-static action**

Anchor size			M6	M8	M10	M12
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,2			
<b>Steel failure</b>						
Characteristic tension resistance, steel zinc plated	$N_{Rk,s}$	[kN]	16,1	22,6	26,0	56,6
Partial safety factor	$\gamma_{Ms}$	[-]	1,5			
Characteristic tension resistance, stainless steel A4, HCR	$N_{Rk,s}$	[kN]	14,1	25,6	35,8	59,0
Partial safety factor	$\gamma_{Ms}$	[-]	1,87			
<b>Pull-out failure</b>						
Characteristic resistance in cracked concrete C20/25	$N_{Rk,p}$	[kN]	5	9	12	20
Increasing factor	$\psi_c$	[-]	$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$			
<b>Concrete cone failure</b>						
Effective anchorage depth	$h_{ef}$	[mm]	45	58	65	80
Factor according to CEN/TS 1992-4	$k_{cr}$	[-]	7,2			

**Heavy duty anchor BZ-IG**

**Performance**  
Characteristic values for tension loads, BZ-IG, cracked concrete, static and quasi-static action

**Annex C11**

**Table C12: Characteristic values for tension loads, BZ-IG, non-cracked concrete, static and quasi-static action**

Anchor size			M6	M8	M10	M12
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,2			
<b>Steel failure</b>						
Characteristic tension resistance, steel zinc plated	$N_{Rk,s}$	[kN]	16,1	22,6	26,0	56,6
Partial safety factor	$\gamma_{Ms}$	[-]	1,5			
Characteristic tension resistance, stainless steel A4, HCR	$N_{Rk,s}$	[kN]	14,1	25,6	35,8	59,0
Partial safety factor	$\gamma_{Ms}$	[-]	1,87			
<b>Pull-out</b>						
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,p}$	[kN]	12	16	20	30
<b>Splitting</b> ( $N_{Rk,c}^0$ has to be replaced by $N_{Rk,sp}^0$ . The higher resistance of Case 1 and Case 2 may be applied.)						
Minimum thickness of concrete member	$h_{min}$	[mm]	100	120	130	160
<b>Case 1</b>						
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,sp}^0$	[kN]	9	12	16	25
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]	$3 h_{ef}$			
<b>Case 2</b>						
Characteristic resistance in non-cracked concrete C20/25	$N_{Rk,sp}^0$	[kN]	12	16	20	30
Spacing (edge distance)	$s_{cr,sp} (= 2 c_{cr,sp})$	[mm]	$5 h_{ef}$			
Increasing factor for $N_{Rk,p}$ and $N_{Rk,sp}^0$	$\psi_c$	[-]	$\left(\frac{f_{ck,cube}}{25}\right)^{0,5}$			
<b>Concrete cone failure</b>						
Effective anchorage depth	$h_{ef}$	[mm]	45	58	65	80
Factor according to CEN/TS 1992-4	$k_{ucr}$	[-]	10,1			

**Heavy duty anchor BZ-IG**

**Performance**  
Characteristic values for tension loads, BZ-IG, non-cracked concrete, static and quasi-static action

**Annex C12**

**Table C13: Characteristic values for shear loads, BZ-IG, cracked and non-cracked concrete, static and quasi-static action**

Anchor size			M6	M8	M10	M12
Installation safety factor	$\gamma_2 = \gamma_{inst}$	[-]	1,0			
<b>BZ-IG, steel zinc plated</b>						
<b>Steel failure without lever arm, Installation type V</b>						
Characteristic shear resistance	$V_{Rk,s}$	[kN]	5,8	6,9	10,4	25,8
<b>Steel failure without lever arm, Installation type D</b>						
Characteristic shear resistance	$V_{Rk,s}$	[kN]	5,1	7,6	10,8	24,3
<b>Steel failure with lever arm, Installation type V</b>						
Characteristic bending resistance	$M^0_{Rk,s}$	[Nm]	12,2	30,0	59,8	104,6
<b>Steel failure with lever arm, Installation type D</b>						
Characteristic bending resistance	$M^0_{Rk,s}$	[Nm]	36,0	53,2	76,0	207
Partial safety factor for $V_{Rk,s}$ and $M^0_{Rk,s}$	$\gamma_{Ms}$	[-]	1,25			
Factor of ductility	$k_2$	[-]	1,0			
<b>BZ-IG, stainless steel A4, HCR</b>						
<b>Steel failure without lever arm, Installation type V</b>						
Characteristic shear resistance	$V_{Rk,s}$	[kN]	5,7	9,2	10,6	23,6
Partial safety factor	$\gamma_{Ms}$	[-]	1,25			
<b>Steel failure without lever arm, Installation type D</b>						
Characteristic shear resistance	$V_{Rk,s}$	[kN]	7,3	7,6	9,7	29,6
Partial safety factor	$\gamma_{Ms}$	[-]	1,25			
<b>Steel failure with lever arm, Installation type V</b>						
Characteristic bending resistance	$M^0_{Rk,s}$	[Nm]	10,7	26,2	52,3	91,6
Partial safety factor	$\gamma_{Ms}$	[-]	1,56			
<b>Steel failure with lever arm, Installation type D</b>						
Characteristic bending resistance	$M^0_{Rk,s}$	[Nm]	28,2	44,3	69,9	191,2
Partial safety factor	$\gamma_{Ms}$	[-]	1,25			
Factor of ductility	$k_2$	[-]	1,0			
<b>Concrete pry-out failure</b>						
Factor k acc. to ETAG 001, Annex C or $k_3$ acc. to CEN/TS 1992-4	$k_{(3)}$	[-]	1,5	1,5	2,0	2,0
<b>Concrete edge failure</b>						
Effective length of anchor in shear loading	$l_f$	[mm]	45	58	65	80
Effective diameter of anchor	$d_{nom}$	[mm]	8	10	12	16

**Heavy duty anchor BZ-IG**

**Performance**  
Characteristic values for shear loads, BZ-IG,  
cracked and non-cracked concrete, static and quasi-static action

**Annex C13**



**Table C14: Characteristic values for tension and shear load under fire exposure, BZ-IG, cracked and non-cracked concrete C20/25 to C50/60**

Anchor size		M6	M8	M10	M12		
<b>Tension load</b>							
<b>Steel failure</b>							
<b>Steel zinc plated</b>							
Characteristic resistance	R30	$N_{Rk,s,fi}$	[kN]	0,7	1,4	2,5	3,7
	R60			0,6	1,2	2,0	2,9
	R90			0,5	0,9	1,5	2,2
	R120			0,4	0,8	1,3	1,8
<b>Stainless steel A4, HCR</b>							
Characteristic resistance	R30	$N_{Rk,s,fi}$	[kN]	2,9	5,4	8,7	12,6
	R60			1,9	3,8	6,3	9,2
	R90			1,0	2,1	3,9	5,7
	R120			0,5	1,3	2,7	4,0
<b>Shear load</b>							
<b>Steel failure without lever arm</b>							
<b>Steel zinc plated</b>							
Characteristic resistance	R30	$V_{Rk,s,fi}$	[kN]	0,7	1,4	2,5	3,7
	R60			0,6	1,2	2,0	2,9
	R90			0,5	0,9	1,5	2,2
	R120			0,4	0,8	1,3	1,8
<b>Stainless steel A4, HCR</b>							
Characteristic resistance	R30	$V_{Rk,s,fi}$	[kN]	2,9	5,4	8,7	12,6
	R60			1,9	3,8	6,3	9,2
	R90			1,0	2,1	3,9	5,7
	R120			0,5	1,3	2,7	4,0
<b>Steel failure with lever arm</b>							
<b>Steel zinc plated</b>							
Characteristic resistance	R30	$M^0_{Rk,s,fi}$	[Nm]	0,5	1,4	3,3	5,7
	R60			0,4	1,2	2,6	4,6
	R90			0,4	0,9	2,0	3,4
	R120			0,3	0,8	1,6	2,8
<b>Stainless steel A4, HCR</b>							
Characteristic resistance	R30	$M^0_{Rk,s,fi}$	[Nm]	2,2	5,5	11,2	19,6
	R60			1,5	3,9	8,1	14,3
	R90			0,7	2,2	5,1	8,9
	R120			0,4	1,3	3,5	6,2

The characteristic resistance for pull-out failure, concrete cone failure, concrete pry-out failure and concrete edge failure can be designed according to TR020 / CEN/TS 1992-4.

**Heavy duty anchor BZ-IG**

**Performance**

Characteristic values for tension and shear loads under fire exposure, BZ-IG cracked and non-cracked concrete C20/25 to C50/60

**Annex C14**

**Table C15: Displacements under tension load, BZ-IG**

Anchor size			M6	M8	M10	M12
Tension load in cracked concrete	N	[kN]	2,0	3,6	4,8	8,0
Displacements	$\delta_{No}$	[mm]	0,6	0,6	0,8	1,0
	$\delta_{Ncr}$	[mm]	0,8	0,8	1,2	1,4
Tension load in non-cracked concrete	N	[kN]	4,8	6,4	8,0	12,0
Displacements	$\delta_{No}$	[mm]	0,4	0,5	0,7	0,8
	$\delta_{Ncr}$	[mm]	0,8	0,8	1,2	1,4

**Table C16: Displacements under shear load, BZ-IG**

Anchor size			M6	M8	M10	M12
Shear load in cracked and non-cracked concrete	V	[kN]	4,2	5,3	6,2	16,9
Displacements	$\delta_{Vo}$	[mm]	2,8	2,9	2,5	3,6
	$\delta_{Vcr}$	[mm]	4,2	4,4	3,8	5,3

**Heavy duty anchor BZ-IG**

**Performance**  
Displacements under tension load and under shear load

**Annex C15**